



- FW= Frame width  
Min. 928 / max. 2428
- FH= Frame height  
Min. 2100 / max. 2400
- COW= Clear opening width  
COW=FW-27
- COH= Clear opening height  
COH=FH
- CL= Cover length

- State when ordering
- FW=.....mm
  - FH=.....mm
  - COW=.....mm
  - COH=.....mm
  - Cover Yes
  - CL=.....mm
  - Midrail 70 Yes
  - Midrail 150 Yes
  - MH=.....mm
  - Bottom rail 178 Yes

- Surface treatment
- Silver anodized
  - Special anodized.....
  - RAL.....
  - Special powder coating.....
  - .....

- Glass
- 6 mm laminated glass
  - 8 mm laminated glass
  - 6 mm tempered glass
  - 8 mm tempered glass

- (Rectangular glazing beads)
- 6/10/6 mm Insulated lam. glass
  - 8/24/8 mm Insulated lam. glass

- Lock
- ASSA 2-way Yes
  - Euro 1-way Yes
  - Euro 2-way Yes

Insulated glass

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

Besam ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**ADS Automatic Door System**  
**Frame reverse break-out UniSlide**  
**2 Panel wall mounted**  
**Article No. 100210**



**B** **1000108**