



FW= Frame width  
Min. 1800 / max. 3000  
 $FW=2COW+88+X$

FH= Frame height  
Min. 1900 / max. 3000

X= Distance to avoid finger trap (100 mm)  
Distance to avoid head trap (200 mm)

COW= Clear opening width  
 $COW=(FW-88-X)/2$

COH= Clear opening height  
 $COH=FH$

CL= Cover length

State when ordering

- FW=.....mm  
FH=.....mm  
X=.....mm  
COW=.....mm  
COH=.....mm  
Cover Yes   
CL=.....mm  
Midrail 70 Yes   
Midrail 150 Yes   
MH=.....mm  
Bottom rail 178 Yes

Surface treatment

- Silver anodized   
Special anodized.....  
RAL.....  
Special powder coating.....  
.....

Glass

- 6 mm laminated glass   
8 mm laminated glass   
6 mm tempered glass   
8 mm tempered glass

(Rectangular glazing beads)

- 6/10/6 mm Insulated lam. glass   
8/24/8 mm Insulated lam. glass   
Thermo profiles

Lock

- ASSA 2-way Yes   
Euro 1-way Yes   
Euro 2-way Yes

Scale 1:5

Customer:

Besam ref:

Door id:

Date:

Project No:

Sign:

**Frame UniSlide**  
**ADS Automatic door system**  
**2 Panel wall mounted left**  
**Article No. 800056**



F

832969