

FW= Frame width
Min. 1800 / max. 6000
 $FW=2COW+160+2X$

FH= Frame height
Min. 2050 / max. 3150

X= Distance to avoid finger trap (100 mm)
Distance to avoid head trap (200 mm)

COW= Clear opening width
 $COW=(FW-160-2X)/2$

COH= Clear opening height
 $COH=FH-156$

CL= Cover length


State when ordering
FW=.....mm
FH=.....mm
X=.....mm
COW=.....mm
COH=.....mm
Cover Yes
CL=.....mm
Midrail 70 Yes
Midrail 150 Yes
MH=.....mm
Bottom rail 178 Yes

Surface treatment
Silver anodized
Special anodized.....
RAL.....
Special powder coating.....

Glass
6 mm laminated glass
8 mm laminated glass
6 mm tempered glass
8 mm tempered glass

(Rectangular glazing beads)
6/10/6 mm Insulated lam. glass
8/24/8 mm Insulated lam. glass
Thermo profiles

Lock
ASSA 2-way Yes
Euro 1-way Yes
Euro 2-way Yes



Scale 1:5

Customer: _____
Door id: _____
Project No: _____

Besam ref: _____
Date: _____
Sign: _____

ADS Automatic door system
Frame UniSlide
4 Panel beam mounted
Article No. 800052

besam 

D 832971