



FW= Frame width
Min. 1800 / max. 3000
FW=2COW-127-X

FH= Frame height
Min. 2050 / max. 3150

X= Distance to avoid finger trap (100 mm)
Distance to avoid head trap (200 mm)

COW= Clear opening width
COW=(FW-127-X)/2

COH= Clear opening height
COH=FH-156

CL= Cover length

State when ordering
FW=.....mm
FH=.....mm
X=.....mm
COW=.....mm
COH=.....mm
Cover Yes
CL=.....mm
Midrail 70 Yes
Midrail 150 Yes
MH=.....mm
Bottom rail 178 Yes

Surface treatment
Silver anodized
Special anodized.....
RAL.....
Special powder coating.....

Glass
6 mm laminated glass
8 mm laminated glass
6 mm tempered glass
8 mm tempered glass

(Rectangular glazing beads)
6/10/6 mm Insulated lam. glass
8/24/8 mm Insulated lam. glass
Thermo profiles

Lock
ASSA 2-way Yes
Euro 1-way Yes
Euro 2-way Yes

Scale 1:5

Customer: _____
Door id: _____
Project No: _____

Besam ref: _____
Date: _____
Sign: _____

ADS Automatic door system
Frame UniSlide
2 Panel beam mounted left
Article No. 800053

besam 

F 832972