



- FW= Frame width
Min. 2050 / max. 2800
 $FW=2COW+127+X$
- FH= Frame height
Min. 2100 / max. 2400
- X= Min. safety distance 160 mm
- COW= Clear opening width
 $COW=(FW-127-X)/2$
- COH= Clear opening height
 $COH=FH-55$
- CL= Cover length

- State when ordering
- FW=.....mm
 - FH=.....mm
 - X=.....mm
 - COW=.....mm
 - COH=.....mm
 - CL=.....mm
 - Midrail 70
 - Midrail 150
 - MH=.....mm
 - Bottom rail 178
- Surface treatment
- Silver anodized
 - Special anodized.....
 - RAL.....
 - Special powder coating.....
 -

- Glass
- 6 mm laminated glass
 - 8 mm laminated glass
 - 6 mm tempered glass
 - 8 mm tempered glass
- (Rectangular glazing beads)
- 6/10/6 mm Insulated lam. glass
 - 8/24/8 mm Insulated lam. glass
- Lock
- ASSA 2-way
 - Euro 1-way
 - Euro 2-way

Scale 1:5

Customer: _____

Door id: _____

Project No: _____

Besam ref: _____

Date: _____

Sign: _____

ADS Automatic door system
Frame break-out UniSlide
2 Panel wall mounted left
Article No. 800080

besam

F 832979