



FW= Frame width  
Min. 2050 / max. 2800  
 $FW=2COW+127+X$

FH= Frame height  
Min. 2250 / max. 2550

X= Min. safety distance 160 mm

COW= Clear opening width  
 $COW=(FW-127-X)/2$

COH= Clear opening height  
 $COH=FH-161$

CL= Cover length

State when ordering

FW=.....mm  
FH=.....mm  
X=.....mm  
COW=.....mm  
COH=.....mm  
CL=.....mm

- Midrail 70
- Midrail 150
- MH=.....mm
- Bottom rail 178

Surface treatment

- Silver anodized
- Special anodized.....
- RAL.....
- Special powder coating.....
- .....

Glass

- 6 mm laminated glass
- 8 mm laminated glass
- 6 mm tempered glass
- 8 mm tempered glass

(Rectangular glazing beads)

- 6/10/6 mm Insulated lam. glass
- 8/24/8 mm Insulated lam. glass

Lock

- ASSA 2-way
- Euro 1-way
- Euro 2-way

Scale 1:5

Customer:

Besam ref:

Door id:

Date:

Project No:

Sign:

**ADS Automatic door system**  
**Frame break-out UniSlide**  
**2 Panel beam mounted left**  
**Article No. 800083**



G

832982