



FW= Frame width  
Min. 1600 / max. 3600  
FW=COW+22

FH= Frame height  
Min. 1900 / max. 3000

COW= Clear opening width  
COW=FW-22

COH= Clear opening height  
COH=FH

CL= Cover length

State when ordering  
FW=.....mm  
FH=.....mm  
COW=.....mm  
COH=.....mm  
Cover Yes   
CL=.....mm  
Midrail 70 Yes   
Midrail 150 Yes   
MH=.....mm  
Bottom rail 178 Yes

Surface treatment  
Silver anodized   
Special anodized.....  
RAL.....  
Special powder coating.....  
.....

Glass  
6 mm laminated glass   
8 mm laminated glass   
  
(Rectangular glazing beads)  
6/10/6 mm Insulated lam. glass   
8/24/8 mm Insulated lam. glass   
Thermo profiles

Lock  
ASSA 2-way Yes   
Euro 1-way Yes   
Euro 2-way Yes

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

Besam ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**ADS Automatic door system**  
**Frame telescopic UniSlide**  
**4 Panel wall mounted**  
**Article No. 800152**

