



FW= Frame width
 Min. 2800 / max. 6000
 $FW=1,5COW+165+2X$

FH= Frame height
 Min. 1900 / max. 3000

X= Distance to avoid finger trap (100 mm)
 Distance to avoid head trap (200 mm)

COW= Clear opening width
 $COW=(2FW-4X-330)/3$

COH= Clear opening height
 $COH=FH$

CL= Cover length

State when ordering

- FW=.....mm
 FH=.....mm
 X=.....mm
 COW=.....mm
 COH=.....mm
 Cover Yes
 CL=.....mm
 Midrail 70 Yes
 Midrail 150 Yes
 MH=.....mm
 Bottom rail 178 Yes

Surface treatment

- Silver anodized
 Special anodized.....
 RAL.....
 Special powder coating.....

Glass

- 6 mm laminated glass
 8 mm laminated glass

(Rectangular glazing beads)

- 6/10/6 mm Insulated lam. glass
 8/24/8 mm Insulated lam. glass
 Thermo profiles

Lock

- ASSA 2-way Yes
 Euro 1-way Yes
 Euro 2-way Yes

Customer: _____
 Door id: _____
 Project No: _____

Besam ref: _____
 Date: _____
 Sign: _____

ADS Automatic door system
Frame telescopic UniSlide
6 Panel wall mounted
Article No. 800155

