

- FW= Frame width
Min. 1600 / max. 4800
 $FW=1,5COW+92+X$
- FH= Frame height
Min. 1900 / max. 3000
- X= Distance to avoid finger trap (100 mm)
Distance to avoid head trap (200 mm)
- COW= Clear opening width
 $COW=(2FW-2X-184)/3$
- COH= Clear opening height
 $COH=FH$
- CL= Cover length

- State when ordering
- FW=.....mm
 - FH=.....mm
 - X=.....mm
 - COW=.....mm
 - COH=.....mm
 - Cover Yes
 - CL=.....mm
 - Midrail 70 Yes
 - Midrail 150 Yes
 - MH=.....mm
 - Bottom rail 178 Yes

- Surface treatment
- Silver anodized
 - Special anodized.....
 - RAL.....
 - Special powder coating.....

- Glass
- 6 mm laminated glass
 - 8 mm laminated glass
 - (Rectangular glazing beads)
 - 6/10/6 mm Insulated lam. glass
 - 8/24/8 mm Insulated lam. glass
 - Thermo profiles

- Lock
- ASSA 2-way Yes
 - Euro 1-way Yes
 - Euro 2-way Yes

Customer: _____

Door id: _____


Project No: _____

Besam ref: _____

Date: _____

Sign: _____

ADS Automatic door system
Frame telescopic UniSlide
3 Panel wall mounted left
Article No. 800156



G **832988**