

FW= Frame width  
 Min. 2800 / max. 6000  
 $FW=1,5COW+165+2X$


FH= Frame height  
 Min. 2050 / max. 3150

X= Distance to avoid finger trap (100 mm)  
 Distance to avoid head trap (200 mm)

COW= Clear opening width  
 $COW=(2FW-4X-330)/3$

COH= Clear opening height  
 $COH=FH-156$

CL= Cover length



State when ordering

- FW=.....mm
- FH=.....mm
- X=.....mm
- COW=.....mm
- COH=.....mm
- Cover Yes
- CL=.....mm
- Midrail 70 Yes
- Midrail 150 Yes
- MH=.....mm
- Bottom rail 178 Yes

Surface treatment

- Silver anodized
- Special anodized.....
- RAL.....
- Special powder coating.....

Glass

- 6 mm laminated glass
- 8 mm laminated glass

(Rectangular glazing beads)

- 6/10/6 mm Insulated lam. glass
- 8/24/8 mm Insulated lam. glass
- Thermo profiles

Lock

- ASSA 2-way Yes
- Euro 1-way Yes
- Euro 2-way Yes

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

Besam ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**ADS Automatic door system**  
**Frame telescopic UniSlide**  
**6 Panel beam mounted**  
**Article No. 800158**



**D** **832990**