



FW= Frame width  
 Min. 1800 / max. 3000  
 $FW=2COW+35+X$

FH= Frame height  
 Min. 2100 / max. 3150

X= Distance to avoid finger trap (25 mm)

COW= Clear opening width  
 $COW=(FW-35-X)/2$

COH= Clear opening height  
 $COH=FH-195$

CL= Cover length

State when ordering  
 FW=.....mm  
 FH=.....mm  
 X=.....mm  
 COW=.....mm  
 COH=.....mm  
 Cover  
 CL=.....mm

Surface treatment  
 Silver anodized  
 Special anodized.....  
 RAL.....  
 Special powder coating.....  
 .....

Glass  
 8 mm laminated glass  
 10 mm laminated glass  
 12 mm laminated glass  
 8 mm tempered glass  
 10 mm tempered glass

Lock  
 Floor lock Euro 1-way  
 Floor lock Euro 2-way

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

Besam ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**ADS Automatic door system**  
**Slim UniSlide**  
**2 Panel beam mounted right**  
**Article No. 800096**

**besam** 

**F** **833001**