



FW= Frame width  
 Min. 2800 / max. 6000  
 $FW=(3COW+115+4X)/2$

FH= Frame height  
 Min. 1950 / max. 3000

X= Safety distance (50 mm)

COW= Clear opening width  
 $COW=(2FW-115-4X)/3$

COH= Clear opening height  
 $COH=FH-50$

CL= Cover length

State when ordering  
 FW=.....mm  
 FH=.....mm  
 X=.....mm  
 COW=.....mm  
 COH=.....mm  
 Cover Yes   
 CL=.....mm

Surface treatment  
 Silver anodized   
 Special anodized.....  
 RAL.....  
 Special powder coating.....  
 .....

Glass  
 8 mm laminated glass   
 10 mm laminated glass   
 12 mm laminated glass   
 8 mm tempered glass   
 10 mm tempered glass

Lock  
 Floor lock Euro 1-way Yes   
 Floor lock Euro 2-way Yes

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

Besam ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**ADS Automatic door system**  
**Slim telescopic UniSlide**  
**6 Panel wall mounted**  
**Article No. 800223**

**besam** 

**D** **833060**